

```
!  
! Last configuration change at 12:05:07 UTC Mon Jan 20 2025 by rpoulet  
!  
version 15.5  
service timestamps debug datetime msec  
service timestamps log datetime msec  
service password-encryption  
!  
hostname R-RO-001  
!  
boot-start-marker  
boot-end-marker  
!  
!  
enable secret 5 $1$PvNR$OVGL3NOYXS76ld12RY6Dd.  
!  
no aaa new-model  
ethernet lmi ce  
!  
!  
!  
!  
!  
!  
!  
!  
!  
!  
!  
no ip domain lookup  
ip domain name romemedilab.fr  
ip cef  
no ipv6 cef  
!  
multilink bundle-name authenticated  
!  
!  
!  
!  
license udi pid CISCO2921/K9 sn FCZ181370ET  
hw-module usb disable  
!  
!  
username imoufidi privilege 15 secret 5 $1$RCRB$fhKnRw6X0CswKyF3ObBcd1  
username tguyot privilege 15 secret 5 $1$cRzA$zY6lwxSO4koQpamuCOo0j1  
username rpoulet privilege 15 secret 5 $1$wJqs$YmTrPJfXSy17FNIMjAPei1  
!  
redundancy  
!  
!  
!  
!  
!
```



```
ip address 172.16.32.46 255.255.255.240
ip helper-address 172.16.32.42
ip helper address 172.16.32.43
ip nat inside
ip virtual-reassembly in
!
```

```
interface GigabitEthernet0/0.130
description CLOUD
encapsulation dot1Q 130
ip address 172.16.32.62 255.255.255.240
ip helper-address 172.16.32.42
ip helper address 172.16.32.43
ip nat inside
ip virtual-reassembly in
!
```

```
interface GigabitEthernet0/0.140
description vlan 140
encapsulation dot1Q 140
ip address 172.16.32.78 255.255.255.240
ip helper-address 172.16.32.42
ip helper address 172.16.32.43
ip nat inside
ip virtual-reassembly in
!
```

```
interface GigabitEthernet0/0.150
description USERS
encapsulation dot1Q 150
ip address 172.16.32.94 255.255.255.240
ip helper-address 172.16.32.42
ip helper address 172.16.32.43
ip nat inside
ip virtual-reassembly in
!
```

```
interface GigabitEthernet0/0.160
description SUPERVISION
encapsulation dot1Q 160
ip address 172.16.32.110 255.255.255.240
ip helper-address 172.16.32.42
ip helper address 172.16.32.43
ip nat inside
ip virtual-reassembly in
!
```

```
interface GigabitEthernet0/0.170
description SAUVEGARDE
encapsulation dot1Q 170
ip address 172.16.32.126 255.255.255.240
ip helper-address 172.16.32.42
ip helper address 172.16.32.43
ip nat inside
ip virtual-reassembly in
!
```

```
interface GigabitEthernet0/0.180
description BDD
encapsulation dot1Q 180
ip address 172.16.32.142 255.255.255.240
```

```
ip helper-address 172.16.32.42
ip helper address 172.16.32.43
ip nat inside
ip virtual-reassembly in
!
interface GigabitEthernet0/0.190
description WEB
encapsulation dot1Q 190
ip address 172.16.32.158 255.255.255.240
ip helper-address 172.16.32.42
ip helper address 172.16.32.43
ip nat inside
ip virtual-reassembly in
!
interface GigabitEthernet0/0.200
description GESTION
encapsulation dot1Q 200
ip address 172.16.32.174 255.255.255.240
ip helper-address 172.16.32.42
ip helper address 172.16.32.43
ip nat inside
ip virtual-reassembly in
!
interface GigabitEthernet0/0.210
description RESSOURCES
encapsulation dot1Q 210
ip address 172.16.32.190 255.255.255.240
ip helper-address 172.16.32.42
ip helper address 172.16.32.43
ip nat inside
ip virtual-reassembly in
!
interface GigabitEthernet0/1
description vers internet
ip address dhcp
ip nat outside
ip virtual-reassembly in
duplex auto
speed auto
!
interface GigabitEthernet0/2
no ip address
shutdown
duplex auto
speed auto
!
ip forward-protocol nd
!
no ip http server
no ip http secure-server
!
ip nat inside source list 1 interface GigabitEthernet0/1 overload
ip ssh time-out 60
ip ssh version 2
!
```

```
!  
!  
access-list 1 permit 172.16.32.0 0.0.0.255  
!  
control-plane  
!  
!  
banner motd Acces interdit aux personnes non autorisees  
!  
line con 0  
  login local  
line aux 0  
line 2  
  no activation-character  
  no exec  
  transport preferred none  
  transport output pad telnet rlogin lapb-ta mop udptn v120 ssh  
  stopbits 1  
line vty 0 1  
  login local  
  transport input ssh  
line vty 2 4  
  login  
  transport input none  
!  
scheduler allocate 20000 1000  
!  
end
```